

PRODUCT INFORMATION

PART NUMBER:

Varies with colour and packing.

DESCRIPTION:

Circular 13-core: 1 x 2.5mm² (35/0.3mm) + 12 x 1.5mm² (21/0.3mm); Plain Copper, TWA PVC Insulated, HR PVC Sheathed.

CONDUCTORS:

Plain annealed copper bunch meeting the requirements of ISO 6722.
12 cores, 1.5mm² (21/0.3mm).
1 core, 2.5mm² (35/0.3mm).

INSULATION:

"Thin wall auto grade" PVC compound, formulated without lead based additives meeting the requirements of ISO 6722, Class B.
Minimum thickness (1.5mm²) = 0.24mm;
(2.5mm²) = 0.28mm.

LAY UP:

Centre: White (2.5mm²), Yellow (1.5mm²), Blue (1.5mm²).
Outer: (1.5mm²), (Dark) Green, Brown, Red/Black, Black, Red, Pink, Violet, Grey, Light Brown, Orange.

SCREEN:

Not Applicable.

SHEATH:

PVC compound, formulated without lead based additives meeting the requirements of ISO 6722, Class A.
Minimum overall diameter = 12.0mm.
Maximum overall diameter = 12.7mm.

SERVICE DATA:

For use in road vehicles.
Maximum Rated Voltage: 60V d.c. or 25V a.c.
Maximum conductor operating temperature: 100°C.
Minimum operating temperature: -40°C.
Approximate Mass/Unit Length: 298kg/km.